
Telemecanique Sensors

A Trusted Specialist Providing
Reliable Sensing Solutions.



Simply easy!

Telemecanique Sensors & Square D Limit Switches & Fluid Control:



Inductive

- One of the most comprehensive product lines on the market
- Standard cylindrical forms: M8, 12, 18, 30
- Standard rectangular and flat forms
- Top quality enclosures up to IP69K rating
- Available in standard and increased sensing range
- Constructed for durability in harsh environments
- New one-piece 303/316L stainless steel and WFI proximity sensors



Photoelectric

- Available in thru-beam, polarized retro reflective, proximity diffuse and diffuse w/background suppression
- Multi-mode sensors that can switch between modes
- Application specific sensors for transparent material detection, label sensing, color detection, color mark reading, distance measurement & much more.
- Cost-effective and easy to install Fork Sensors
- Vision sensor to assist quality control



Ultrasonic

- Industry leading technology
- Uses sound to detect objects control level, or provide analog output signal for continuous monitoring.
- Non-contact with materials in the sensing environment
- Immune to changing light conditions, colors, dust, splashing materials or liquids



Limit Switches

- A leading supplier of top quality limit switches for over 90 years: Square D and Telemecanique brands
- Broad range of options and accessories
- Offering heavy duty, compact, miniature and application-specific limit switches
- New wireless and batteryless Limit Switch now available!



IEC Limit Switches

- Meet IEC standards and are accepted globally.
- Meet domestic and other international standards including NEMA, UL, CSA, VDE and more.
- Miniature, compact, and industrial switches for general, medium, and heavy-duty apps.
- Variety of operating heads, contact configurations, and lever arms. Versions for automated applications, safety, and environments with shock and vibration.



NEMA Limit Switches

- Our proven line of 9007C limit switches can withstand heavy-industry demands.
- Rugged and Dependable, our switches are built with unparalleled quality.
- Available in Standard Industrial Heavy Duty, Miniature potted, and Severe Duty Enclosures.
- With a broad range of options and accessories our NEMA line provides virtually unparalleled flexibility.

Providing solutions for the Industrial Marketplace for over 90 years.



FOOD &
BEVERAGE



PUMPING



HVAC



ELEVATORS /
ESCALATORS



CRANE & HOIST



Capacitive

- Detection of objects irrespective of material or conductivity
- Ideal for sensing non-metal objects for level control of fluids and granular material
- Sensitivity can be adjusted to detect bulk materials or a liquid level “through” another object.



Radio Frequency Identification (RFID)

- Enables object traceability, identification (tracking) and access controls
- Compatible with other manufacturer RFID components using 13.56 Mhz frequency components, including tags
- Automatic setting of speed, format, parity, & protocol communication parameters.
- Network connection boxes that support Modbus TCP/IP, Ethernet IP and Profibus-DP PLC



Encoders

- Incremental & absolute products
- Configurable models easy to select with adjustable resolution & a 1 to 16 multiplication factor.
- Push-pull 5 to 30 V wide range output.
- Simplified installation using M23 connection and market standard compatible mountings.
- Mechanical flexibility using modular solid or hollow shafts up to 15 mm
- High performance, up to 25 bits & up to 8,000 pts per rev.
- CANopen and PROFIBUS-DP full compatibility



Fluid Control

- Wide variety of pressure and float switches and sensors give you the right choices for both simple and complex fluid control applications with time proven performance and reliability
- The innovative, compact construction simplifies installation while providing a long service life.
- Rugged design provides solutions suitable for even the most demanding applications and environments



IEC Fluid Control

- Comprehensive range provides versatile solutions for a wide variety of fluid control applications.
- Conforms to IEC standards, and are globally recognized and accepted.
- User-friendly electronic transmitters and switches offer robust, accurate, reliable and cost effective pressure measurement
- Compact design provides easy installation & reduces mounting space



NEMA Fluid Control

- The trusted, reliable and rugged Square D brand
- Time-proven performance
- Square D™ brand pressure, vacuum, and float switches meet most domestic and international standards, including NEMA, UL, CSA, CE
- Simple installation and rugged design suitable for demanding applications and environments
- Wide range of options and accessories

SQUARE D[™]
by Schneider Electric


Telemecanique Sensors solutions for enhanced machine safety



PACKAGING



Safety Limit Switches

- Protects personnel in guarding applications where contact with the guard is required.
- Featuring positive opening contact operation  and tamper resistant mounting
- Interrupt machine or control processes when the switch plunger or lever is deflected by the sliding action of the guard or other object.
- Available in miniature or compact with plastic or metal bodies.



Light Curtains

- Point of operation protection around industrial machinery or guarding of large areas without the need for gates or guards.
- Ideal for safeguarding larger areas without impeding visibility or easy access to the machine.
- XUSL4E and XUSL2E light curtains feature either 14 mm or 30 mm MOS with a slim design for locations with limited space.



MATERIAL HANDLING



METAL WORKING



Safety Interlock Switches

- Protects personnel by verifying that doors, gates and guards are closed before starting a process.
- Minimize accidents by removing the actuating key and sending a stop signal to the safety circuit when the guard or gate is open.
- Simple to install & configure, feature metal or plastic bodies and can be used with an assortment of actuating keys meeting domestic and international standards.



Cable Pull Switches

- Enables an emergency stop to be signaled at any point along cables extending up to 650 ft.
- Simple to operate and install
- Provides emergency stop (where switch actuation locks the contacts in the open position & requires manual reset) or normal stop operation, for momentary, system stoppage.
- Meet ISO 13850 requirements (relating to emergency stop) and North American standards also.



MATERIAL WORKING



AUTOMOTIVE



Non-contact Safety Interlock Switches

- For use when there is no contact desired between the switch and its actuating key.
- Tamper-resistant & suitable for all safety circuits, these interlocks tolerate misalignment of doors or guards without placing operating forces on gates or doors.
- Feature multiple mounting options for maximum flexibility.
- Small and sealed: ideal for confined spaces or washdown.



Connectivity

- Pre-wired connectors: for easy connection of sensors with connectors to terminal blocks or PLC inputs
- Connectors: for connecting a cable of usable length to a sensor with connectors
- Jumper cables: for connecting sensors with connectors to splitter blocks
- Connector adaptors: transform a sensor with terminals into a sensor with connectors

Telemecanique Sensors USA

1875 Founders Dr.
Dayton, OH 45420-4017
TEL: 888-778-2733

www.tesensors.us

Telemecanique Sensors Canada

5985 McLaughlin Road
Mississauga, Ontario L5R 1B8
TEL: 800-565-6699

www.tesensors.ca

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.